



# Lettore QR per Green Pass

AC-QRGP



## Specifiche tecniche

Image (pixels)	640(H)x480(V)
Light Source	Illumination: 6500K LED
Field of View	75° (H)x60°(V)
Roll/Pitch/Yaw	360°, ± 60°, ± 60°
Interface	USB, TTL232
Print Contrast	20%minimum reflective difference
Motion Tolerances	Up to 300cm/s
1D QR Code	+UPC/EAN, UPN/EAN with supplementals, Code128, GSI-128, Code 39, Trioptic, Code 32, Code 93, Code11, Matrix 2 of 5, Interleaved 2 of 5, IATA 2 of 5, Industrial 2 of 5, Codabar, Codablock F, MSI, Telepen, Code11, GSI DataBar variants, etc
2D QR Code	QR Code, PDF417, MicroPDF417, Composite Code, Date Matrix, Maxicode, MicroQR, Aztec, etc
Operating Temperature	-20 °C ~ 60 °C
Storage Temperature	-40 °C ~ 70 °C
Storage Humidity	0% -95% Non-condensing
Shock Specification	Dedigned to withstands 1.5m(5') drops
Ambient Light	Immunity 100,000Lux
Decode Range	EAN13 13MIL: 5mm-140mm, Code39 5MIL: 20mm-48mm, Code39 20MIL: 30mm-180mm, 1D Minimal: 5mil 1D(Performance may be impacted by barcode quality and enviromental conditions)