



DATASHEET
STAMPANTE
TERMICA ESC/POS

MODEL: BP-DTPP-009

FEATURES

- Light weight and portable
- Beautiful shape
- Low cost and High-quality thermal printing
- Cash drawer drive supported
- Easy paper-roll installation, Easy maintenance and Rational structure
- Low-power waste, low-run cost (without the ribbons, ink cartridges)
- Built-in data buffers (be capable of receiving print data while printing)
- Characters can be amplified, printed in bold optionally, and line spacing printing can be adjusted
- Support different density bitmap graphics printing
- Support NV image downloading and printing
- Support raster bitmap printing
- High-speed printing using embedded soft font for all interfaces.
- Compatible with ESC/POS print instruction set, optional columns and font(adjusted by DIP

Advantage Characteristics

- Audible and visual alarm supported, best application for kitchen menu printing.
- USB port, Serial port, and Ethernet interface integrated on a main board.

SPECIFICATION

| Printing Method | Thermal line printing |
|----------------------------|--|
| Character size | 512 dots/line |
| FontA | 12x24dots, 1.5(W)x3.0(H)mm |
| FontB | 9x17dots, 1.1(W)x2.1(H)mm |
| Simplified/Traditional | 24x24dots,3.0(W)x3.0(H)mm |
| Print parameters | support to download the Logo trademark |
| Printing Chinese character | Chinese= simplified Chinese 24x24 point. support 18030 font library, |
| | support Taiwan and HK traditional(complex font) |
| ANK | ANK characters |
| Extended character table | OEM437 / Katakana / OEM850 / OEM860 / OEM863 / OEM865 / West Europe |
| | Greek / Hebrew / EastEurope / Iran / WPC1252 / OEM866 / OEM852 |
| | OEM858 / IranlI / Latvian / Arabic / PT1511251 / OEM747 / WPC1 257 |
| | Vietnam / OEM864 / Hebrew / WPC1255 / Thai |
| Barcode Types | UPC-A/UPC-E/JAN13(EAN13) / JAN8(EAN8) CODABAR /ITF/ CODE39 |
| | CODE93 / CODE128 |

| Print Speed | 300mm/second |
|--------------------|---|
| Interface | Serial port/USB port/ Ethernet |
| Emulation | ESC/POS command |
| Print width | 79.5±0.5mm(print width 72mm) |
| Print Diameter | 83mm |
| Print thickness | 0.06-0.08mm |
| Power | DC24V/2.5A |
| Cutter | Full or Partial cut |
| Reliability print | 100km Weight |
| Temperature | 0-45°C |
| Contrast humidity | 10-80% |
| Drivers | Win9X / Win2000 / Win2003 / Win Vista / Win 7 / Window XP / Windows 8 |
| | Linux Compatible with ESPON, SAMSUNG |
| External Dimension | 190x145x145mm (LxWxH) |