



# Thermal Receipt Printer

BP-DTPP-020



## Features

- High Printing Speed up to 300mm/second
- Auto Cutter
- Cord and cordless communication for options
- Multiple interfaces available: USB + Serial + LAN
- Sound and light alarm supported suitable for kitchen application
- Support multiple 1D and QR code types printing
- Support multi international languages
- SDK for Android available
- Reliable printer head with 100km life
- Compatible with EPSON ESC/POS commands

## Technical specification

Printing Method	Thermal line printing
Printing Character	576dots/line (default), 512dots/line; Characters : Simplified Chinese 24x24 point, support 18030 font library, support Taiwan and HK traditional (complex font), ANK characters
Font	A: 12 x 24 dots,1.5(W) x 3.0(H) mm B: 9 x 17dots, 1.1(W) x 2.1(H) mm Simplified/Traditional : 24x 24dots, 3.0(W) x 3.0(H) mm
Barcode Type	JUPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODABAR/ITF/C ODE39/CODE93/CODE128, QR code
Printing Speed	250mm/sec for a single interface ,300mm/sec forthree interfaces
Interface	USB + Serial + LAN
Printing Command	Compatible with EPSON ESC/POS commands
Drivers	Win9X / Window XP / Win2000 / Win2003 / Win Vista / Win 7 / Win 8 / win8.1 / Linux / Win10, compatible with ESPON, SDK for Android available
Printing Width	79.5 ± 0.5mm (print width 72mm)
Paper Diameter	83mm
Paper Thickness	0.06-0.08mm
Cutter	Auto cutter
Printing Reliability	100km
Power	DC24V/2.5A
Temperature	0-45°C
Contrast Humidity	10-80%
External Dimension	190 x 145 x 145 mm
Weight	1.60kg