

machpower®



SCHEDA TECNICA

UNMANAGED SWITCH 120W

8 x 10/100Mbps POE 24V + 1 x Uplink port 10/100Mbps

MODELLO: SW-UF8P24-048

DESCRIZIONE

Switch 8 porte 10/100Mbps + 1 porta Up-Link 10/100Mbps, struttura in metallo progettato per installazione su desktop o rack, ideale per alimentare e trasferire dati ad Access Point o altri dispositivi PoE 24V.

Switch 8 porte 24V Plug&Play, tutte le porte supportano auto-negotiation, auto MDI/MDIX, ideale per soluzioni networking per ambienti domestici e professionali.

CARATTERISTICHE PRINCIPALI

Semplice installazione su desktop o rack

8 porte 24V passive PoE 10/100Mbps + 1 porta 10/100Mbps Up-Link

Alimenta dispositivi 24V passive PoE fino ad un massimo 120W

SPECIFICHE

Ports	9 x auto Negotiation /auto MDI/MDIX RJ45 Ports
	8 x 10/100Mbps PoE ports
	1 x 10/100Mbps up-link port
Cable requirement	10BASE-T: UTP 3, 4, 5 cable (≤100 meters)
	100BASE-TX: UTP 5 cable (≤100 meters)
POE	120W, 24V-2.5A
LED Indicator	PWR (Power), POE, LINK, ALM (Alarm)
Size (mm)	250(L) x 122(W) x 35(H)
Working Environment	Working Temperature: 0°C ~ 40°C
	Storage Temperature: -40°C ~ 70°C
	Working Humidity: 10% ~ 90% No Condensation
	Storage Humidity: 5% ~ 90% No Condensation
Input Power	24V/2.5A
PoE Standard	IEEE 802.3, 802.3u, 802.3x
	CSMA/CD, TCP/IP

Advanced Functions	Comply with 24V Passive PoE equipment
	Port Priority Function
	MAC Address Auto-Learning and Auto-Aging.
	IEEE802.3X Flow Control for Full-Duplex Mode and Backpressure
	for Half-Duplex Mode
MAC Address Table	2k
Backplane Bandwidth	1.8Gbps
Forwarding Rate	10BASE-T:14880pps/port
	100BASE-TX:148800pps/port