



DATASHEET

10P 10/100M POE SWITCH (1~8P POE)
(1~8P POE) WITH 2 UPLINK PORTS

MODEL: SW-UF8P2LV-067

FEATURES

- 8 x 10/100M Auto-Negotiation RJ45 ports with 8 PoE ports (port-1~port-8) ,
- 2 x 10/100mbps Uplink ports
- 250M cable power Extension and VLAN, support 150W MAX power output
- Supports IEEE 802.3x flow control for Full-duplex Mode and backpressure for Half-duplex Mode
- LED indicators for monitoring power, link, activity and speed
- Desktop mode with Metal Case
- Each POE port Up to 30W of power on(802.3at)
- Compatible With All IEEE 802.3af/at
- Safe: Low Power Devices Receive Only the Power They Need
- Automatic Detection and Protection of Non-standard Ethernet Terminals
- Supports 10/100 Base-T applications
- Plug-and-Play no configuration required
- Internal power supply (100~240V AC ,52V/2.88A output)
- Easy installation and maintenance
- Complies to IEEE 802.3af/at PoE standard and is backward

SPECIFICATION

HARDWARE FEATURES	
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m)
	EIA/TIA-568 100Ω STP (maximum 100m)
	100BASE-TX: UTP category 5, 5e cable (maximum 100m)
	EIA/TIA-568 100Ω STP (maximum 100m)
Interface	10 x 10/100Mbps RJ45 Ports
	AUTO Negotiation/AUTO MDI/MDIX
HARDWARE FEATURES	
PoE Ports (RJ45)	8 (1~8ports)
Backbound Bandwidth	1.6Gbps
Internal Power Supply	Internal Power supply (AC 100~240V,input 52V/2.88A output)
SOFTWARE FEATURES	
Transmission Method	Store-And-Forward
Advanced Functions	Compatible With IEEE 802.3af
	Priority Function
	Mac Address Auto-Learning And Auto-Aging
	IEEE802.3x Flow Control For Full-Duplex Mode And Backpressure For Half-Duplex Mode

OTHERS	
Package Contents	Quick installation Guide, Power adapter
Consumption	Output Power Voltage: 52V
	User Port Power: →15.4Watts /3~600ma,150W output total
Environment	Operating Temperature: 0°C~40°C (32°F~104°F)
	Storage Temperature: -40°C~70°C (-40°F~158°F)
	Operating Humidity: 10%~90% non-condensing
	Storage Humidity: 5%~90% non-condensing