



DATASHEET

5MP POE MOTORIZED VARIFOCAL
AUTOFOCUS IR BULLET

Wi-Fi CAMERA

MODEL: VS-DVB5PMA-259

SPECIFICATION

Camera	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor
Resolution	5MP
Effective Pixels	2616 (H) x 1964 (V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI/MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network
Reset Button	No
Lens Type	
Focus Length	2.7-13.5mm
Focus Control	Auto
Lens Type	Motorized
Pixels	4MP
Night Vision	
Infrared LED	42μx 4PCS
Infrared Distance	40m
IR Status	Auto Control
IR Power On	Auto Control
Network	
Ethernet	RJ-45 (10/100Base-T)
Wireless	/
Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
PoE	Internal, Support IEEE802.3as
Video Delay	0.3S (Within the Lan)
Main Stream 1	2592 x 1944@20fp, 2560 x 1920@20fp
Main Stream 2	2560 x 1440@25fp
Main Stream 3	1920 x 1080@30fps, 1280 x 720@30fps
Sub Stream 1	720 x 480@15fps, 720 x 480@30fps
Sub Stream 2	/

Sub Stream 3	/
Tri Stream	352 x 288@15fps, 352 x 288@30fps
IE Brower	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53), Mac Safari(lower than version 12)
Smart Phone	iPhone, iPad, Android, Android Pad
Camera	
Day/Night	Color/ B&W (IR-CUT)
Intelligence function	/
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control), Video Tampering
Starlight	/
Corridor Pattern	Support
ROI	Support
Defog Mode	Support
BLC	Support
HDR	/
WDR	Support
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/CMS/Web
Language	Multi-language
Interface	
Audio	/
Alarm	/
SD Card Slot	/
RS485	/
General	
Housing	Metal, IP66
Anti-cut Bracket	Yes
IR Cut Filter	Yes
Operation Temperature	-20°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 950mA
Dimension (mm)	275(W) x 91(H) x 80(D)
Weight (g)	1400