

machpower®



DATASHEET
4MP FISH EYE
IP CAMERA IR
MODEL: VS-FE4PSWA-269

SPECIFICATION

Camera	
Image Sensor	1/2.9" SONY Low Illumination CMOS Sensor
Resolution	4MP
Effective Pixels	3096 (H) × 2202 (V)
Compression	H.264/H.265/JPEG/AVI/MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network, CVBS
Reset Button	Yes
Lens Type	
Focus Length	Board Lens 1.05mm
Focus Control	Fixed
Lens Type	Fixed
Pixels	5MP
Night Vision	
Infrared LED	42μx 3PCS
Infrared Distance	20m
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
PoE	Internal POE, Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	2048 x 2048@15fps
Main Stream 2	1520 x 1520@20fps
Main Stream 3	1024 x 1024@20fps
Sub Stream 1	720 x 720@15fps, 720 x 720@20fps
Sub Stream 2	/
Sub Stream 3	/
Tri Stream	512 x 512@15fps, 512 x 512@20fps

IE Brower	IE9-11, Google Chrome(Under Ver 45), Firefox(Under Ver 53), Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad
Wireless	
Antena	3dbi
Hotspot	/
Wi-Fi	Wi-Fi(IEEE802.11b/g/n),2.4Ghz
Wi-Fi Range	No obstacles 300m Max.
Camera Features	
Day/Night	Color/ B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
Corridor Pattern	/
ROI	/
Defog Mode	Support
BLC	Support
HDR	/
WDR	Support
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/NAS/VMS/Web/SD Card
Language	Multi-language
Interface	
Audio	2-way audio(3.5mm audio interface)
Alarm	1channel Input/Ouput
SD Card Slot	support 128G Micro SD With External SD Card Slot
RS485	/
General	
Housing	Body:Metal, Bracket: Plastic
Anti-cut Bracket	No
IR Cut Filter	Yes
Operation Temperature	-20°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 950mA
Dimension (mm)	120(Ø) x 49H)
Weight (g)	500