



DATASHEET

16 CH H.265+ 5IN1

XHVR

MODEL: VS-XHVR16C4K-280

SPECIFICATION

System	
Main Processor	HI3531D
Operating System	Embedded LINUX
Video	
Input	Analog: 16 x (AHD/TVI/CVI: 8MP; TVI/AHD: 5MP; AHD/TVI/CVI: 4MP; AHD/TVI: 3MP; AHD/TVI/CVI: 1080P/720P; Analog: 960H) Analog+Network: 14 x Analog+2 x network(Max 8MP), 12 x Analog+4 x network(Max 8MP), 10 x Analog+6 x network(Max 8MP), 8 x Analog+8 x network(Max 8MP), 6 x Analog+10 x network(Max 8MP), 4 x Analog+12 x network(Max 8MP), 2 x Analog+14 x network(Max 8MP) Network: 32 x network(Max 8MP)(Total incoming bandwidth ≤160M)
Input	16CH BNC
Signal Type	Analog/AHD/CVI/TVI 2.0/TVI 3.0/Network
Output	1 HD,1 VGA
Audio	
Input	6 Channel, RCA
Two-way Audio	No
Output	1 Channel, RCA
Alarm	
Sensor Input	4 Channel
Output	1 Channel
Motion Detection	16 Channel(max 32 Channel in pure network mode)
Trigger Events	Recording, Email, Screen tips, Buzzer, Push notifications(motion detection)
Email Alarm	Send Image to The Designated E-mail
PTZ	
Interface	RS485
Protocol	Pelco-D, Pelco-P
Baud Rate	110~921600
Address	0~255
Display	
VGA	1920 × 1080P /60Hz, 1280 × 1024 /60Hz
HD Output	3840×2160/30Hz, 2560x1440/30Hz, 1920 × 1080P /60Hz, 1280 × 1024/60Hz
Display Split	36 CH/ 25 CH/ 16 CH/ 9 CH/ 8 CH/ 4 CH/ 1 CH
Privacy Masking	3 Rectangular Zones (Each camera)
OSD	Camera title, Time, Video loss, Alarm, Motion detection, Recording

Recording	
Video Compression	H.265/H.265+/H.264/H.264+
Audio Compression	G.711u
Resolution	8MP(3840×2160),5MP(2592×1944),4MP(2560×1440),3MP(2048×1536), 1080P(1920×1080),720P(1280×720),960H(P:960×576/N:960×480)
Video Quality	worst/worse/ordinary/well/best
Record Rate	Analog:PAL:8MP(3840×2160 16 x 8fps),5MP(2592×1944 16 x 12fps), 4MP(2560×1440 16 x 15fps),3MP(2048×1536 16 x 18fps), 1080P(1920×1080 16 x 25fps),720P(1280×720 16 x 25fps), 960H(960×576 16 x 25fps) NTSC:8MP(3840×2160 16 x 8fps),5MP(2592×1944 16 x 12fps), 4MP(2560×1440 16 x 15fps),3MP(2048×1536 16 x 18fps), 1080P(1920×1080 16 x 30fps),720P(1280×720 16 x 30fps), 960H(960×480 16 x 30fps) Pure IP(H.265): PAL:8MP@17×25fps,5MP@26×25fps,4MP@32×25fps, 3MP@32×25fps,1080P@32×25fps,960P@32×25fps,720P@32×25fps, D1@32×25fps NTSC: 8MP@17×30fps,5MP@26×30fps,4MP@32×30fps, 3MP@32×30fps,1080P@32×30fps, 960P@32×30fps, 720P@32×30fps, D1@32×30fps
Record Mode	Manual\Timer\Motion Detection
Playback & Backup	
Decode Capability	9CH 720P@30fps
Sync Playback	Pure Analog: 16CH 8MP@8fps, 16CH 5M@12fps, 16CH 4M@15fps, 16CH 3M@18fps, 16CH 1080p@30fps Mix Mode: 2CH 8MP@30fps, 3CH 5M@30fps, 4CH 4M@30fps, 4CH 3M@30fps, 4CH 1080P@30fps, 4CH 960P@30fps, 4CH 720P@30fps Pure IPC: 2CH 8MP@30fps, 3CH 5M@30fps, 4CH 4M@30fps, 6CH 3M@30fps, 9CH 1080P@30fps, 9CH 960P@30fps, 9CH 720P@30fps 9CH 1080P@30fps, 9CH 960P@30fps, 9CH 720P@30fps
Remote Playback	4 Channel / 1 Channel
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Fast play, Rewind, Digital Zoom, Full screen
Smart Phone Playback	4 Channel
Backup Mode	USB Device(with format FAT 32)/Network/FTP
Network	
Interface	1 RJ45 10M/100/1000M Adaptive Ethernet Interface
Network Functions	TCP/IP, HTTP, UPnP, DNS, NTP, SMTP, PPPoE, DHCP, FTP, DDNS, RTP, RTSP, RTCP

DDNS	Dyndns, changeip, no-ip, Oray, A-PRESS, MYQSEE, SKDDNS, SMART-EYES, ZEBEYE
Web Browser	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53)
CMS Software	Support Windows 7/ Windows 8/Windows 10
Extra Stream	CIF(1~30fps)
Smart Phone	iPhone, ipad, Android, Android pad
Hard Disk Driver	
Interface Type	2 SATA Interface
Capacity	2 SATA Hard Disk (2.5"/3.5" SATA, Up to 16TB)
General	
Language	Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Farisa, German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, korean, Dutch, Greek
UTC Control	Yes
USB Interface	2 USB 2.0 Interfaces
Power consumption	DC 12V
Working Environment	-10~55°C/10~90%
Dimension (W×D×H)	310(W) x 295(D) x 46(H)
Weight (kg)	3.5 (Without HDD)