



4 CH H.265+
5IN1 XHVR

VS-XHVR4C5MN-305



Technical Specification

System	
Main Processor	MC6630
Operating System	Embedded LINUX
Video	
Input	Normal Mode= Analog: 4 x (TVI/AHD= 5M@12fps; AHD/TVI/CVI= 4M@15fps; AHD/TVI= 3M@18fps; AHD/TVI/CVI= 1080P/720P; Analog= 960H)
	Analog+Network= 2 x Analog (TVI/AHD= 5M@12fps; AHD/TVI/CVI= 4M@15fps; AHD/TVI= 3M@18fps; AHD/TVI/CVI= 1080P/720P; Analog= 960H) + 4 x network (MAX 2MP)
	Network= 9 x 5MP/4MP/3MP/1080P/960P/720P (Total incoming bandwidth ≤48M)
Input	4CH BNC
Signal Type	Analog/AHD/CVI/TVI 2.0/TVI 3.0/Network
Output	1HD,1 VGA
Audio	
Input	1 Channel, RCA
Two-way Audio	No
Output	1 Channel, RCA
Alarm	
Sensor Input	No
Output	No
Motion Detection	4 Channel(max 9 Channel in pure network mode)
Trigger Events	Recording, Email, Screen tips, Buzzer, Push notifications(motion detection)
Email Alarm	Send Image to The Designated E-mail
PTZ	
Interface	RS485
Protocol	Pelco-D, Pelco-P
Baud Rate	110~921600
Address	0~255
Display	
VGA	Resolution= 1920 × 1080P/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz,1024 × 768/60Hz
HD Output	Resolution = 1920 × 1080P/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz,1024 × 768/60Hz
Display Split	9 Channel/4 Channel / 1Channel
Privacy Masking	3 Rectangular Zones (Each camera)
OSD	Camera title, Time, Video loss, Alarm, Motion detection, Recording
Recording	
Video Compression	H.265/H.264
Audio Compression	G.711U/G.711A
Resolution	5MP_Lite(1296×1952),4MP_Lite(1280×1440),3MP_Lite(1024×1536),1080N(960×1080),720P(1280×720), 960H(P=960×576/N=960×480)
Video Quality	Lowest/Low/Ordinary/Good/Better/Best
Record Rate	Analog= PAL =5MP_Lite(1296×1944 4 x 8fps),4MP_Lite(1280×1440 4 x 15fps),3MP_Lite(1024×1536 4 x 18fps), 1080N(960x1080 4 x 18fps),720P(1280×720 4 x 20fps), 960H(960×480 4 x 25fps)
	NTSC= 5MP_Lite(1296×1944 4 x 8fps),4MP_Lite(1280×1440 4 x 15fps),3MP_Lite(1024×1536 4 x 18fps), 1080N(960x1080 4 x 18fps),720P(1280×720 4 x 20fps), 960H(960×480 4 x 30fps)
	Pure IP(H.265)= PAL= 5MP@8×25fps,4MP@9×25fps,3MP@9×25fps,1080P@9×25fps,960P@9×25fps, 720P@9×25fps,D1@9×25fps NTSC: 5MP@8×30fps,4MP@9×30fps,3MP@9×30fps,1080P@9×30fps, 960P@9×30fps, 720P@9×30fps, D1@9×30fps
Record Mode	Manual\Timer\Motion Detection

Playback & Backup

Decode Capability	2CH 1080P@30fps
Sync Playback	Pure Analog= 4CH 960H@25fps, 2CH 720P@20fps, 2CH 1080N@18fps, 1CH 5M_LITE@8fps, 1CH 4M_LITE@15fps, 1CH 3M_LITE@18fps Mixture mode= 4CH 720P@25fps, 2CH 1080P@25fps, 1CH 5M_LITE@8fps, 1CH 4M_LITE@15fps, 1CH 3M_LITE@18fps Pure Network= 4CH x 720P@25fps, 2CH 1080P@25fps, 1CH 5MP@25fps
Remote Playback	1 Channel
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Fast play, Slow play, Rewind, Single frame forward/back, Digital Zoom, Full screen
Smart Phone Playback	4 Channel
Backup Mode	USB Device(with format FAT 32)/Network/FTP

Network

Interface	1 RJ45 10M/100M Adaptive Ethernet Interface
Network Functions	TCP/IP, HTTP, UPnP, DNS, NTP, SMTP,DHCP, FTP, DDNS, RTP, RTSP, RTCP
DDNS	Dyndns, changeip, no-ip, Oray, A-PRESS, MYQSEE, SKDDNS, SMART-EYES, ZEBEYE,HDPROVN
Web Browser	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53)
CMS Software	Support Windows 7/ Windows 8/Windows 10
Extra Stream	CIF/D1(1~25fps)
Smart Phone	iPhone, ipad, Android ,Android pad

Hard Disk Driver

Interface Type	1 SATA Interface
Capacity	1 SATA Hard Disk (2.5"/3.5" SATA, Up to 8TB)

General

Language	Simplified Chinese,Traditional Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Japanese, German, French, Portuguese, Turcic, Spanish, Italian, Hungarian, Romanian, korean, Dutch, Greek, Vietnamese
UTC Control	Yes
USB Interface	2 USB 2.0 Interfaces
Power consumption	DC 12V/2A \leq 4W (Without Hard Disk)
Working Environment	-10~55°C /10~90%
Dimension (W×D×H)	260 x 215 x 43(mm)
Weight	2kg (Without HDD)