



SPECIFICATION			
Model NO.	LIRDNTHTC500FK	LIRDNTTHC500FK	
Video Output Mode	AHD/TVI: 5M@20fps/12.5fps, 4M@30fps/15fps, 2M@30fps/25fps; CVI: 4M@30fps/25fps, 2M@30fps/25fps		
Camera	-		
Image Sensor	1/2.5" CMOS sensor	1/2.5" CMOS sensor	
Image Resolution	5M:2592*1944 4M:2560*1440 2M:1920*1080		
TV System	PAL/NTSC	PAL/NTSC	
Electronic Shutter	AUTO	AUTO	
Scanning System	Progressive Scan		
Lens			
Focus Length	2.8-12mm		
Focus Control	Manual		
Lens Type	Varifocal		
Night Vision			
IR Cut Filter	YES		
Infrared LED	14μ x 24PCS		
Infrared Distance	30M		
IR Status	AGC Auto Control		
Camera Features	•		
Starlight			
Day/Night	YES		
OSD Menu	YES		
WDR	DWDR		
итс	YES		
Noise Reduction	DNR		
White Balance	AUTO / MANUAL		
Gain Control	AUTO		
General			
Housing	Metal, IP67		
Bracket	NO	NO	
Operation Temperature	-10°C ~ +60°C RH95% Max	-10°C ~ +60°C RH95% Max	
Storage Temperature	-20°C ~ +60°C RH95% Max	-20°C ~ +60°C RH95% Max	
Power Source	DC12V±10%, 750mA		
Dimension	⊄ 120 x 98(H) mm		
Weight	800g	800g	