



SPECIFICATION

| | | |
|--------------------------|--|----------------------|
| Model NO. | BMSCHTC200FPE | BMSCTHC200FPE |
| Video Output Mode | AHD/TVI: 5M@20fps/12.5fps, 4M@30fps/25fps/15fps, 2M@30fps/25fps; CVI: 4M@30fps/25fps, 2M@30fps/25fps | |
| Camera | | |
| Image Sensor | 1/3" CMOS Sensor | |
| Image Resolution | 5M:2592*1944 4M:2560*1440 2M:1920*1080 | |
| TV System | PAL/NTSC | |
| Electronic Shutter | Auto | |
| Minimum Illumination | Color : 0.03 lux@F2.0, AGC ON; B/W : 0 lux with IR | |
| Scanning System | Progressive Scan | |
| Lens | | |
| Focus Length | 3.6mm | |
| Focus Control | Fixed | |
| Lens Type | Fixed | |
| Night Vision | | |
| IR Cut Filter | YES | |
| Infrared LED | 42μ x 2PCS | |
| Infrared Distance | 25M | |
| IR Status | AGC Auto Control | |
| Camera Features | | |
| Starlight | N/A | |
| Day/Night | YES/NO | |
| OSD Menu | YES | |
| WDR | DWDR | |
| UTC | YES | |
| Noise Reduction | DNR | |
| Coaxial Audio | YES(only TVI) | |
| White Balance | AUTO / MANUAL | |
| Gain Control | AUTO | |
| General | | |
| Housing | Metal, IP67 | |
| Bracket | YES | |
| Operation Temperature | -10°C ~ +60°C RH95% Max | |
| Storage Temperature | -20°C ~ +60°C RH95% Max | |
| Power Source | DC12V±10%, 500mA | |
| Dimension | 70(W) x 67.5(H) x 169(L)mm | |
| Weight | 600g | |