



SPECIFICATION

Model	PT5A018XIGL500
Camera	
Image Sensor	1/2.8" Progressive Scan CMOS Sensor
Horizontal Resolution	5MP
Compression	H.264/H.265/H.264+/H.265+
Minimum Illumination	Color: 0.008 Lux @ (F1.8, AGC ON), B/W: 0 Lux with IR
S/N Ratio	60db
PTZ	
Horizontal Rotation Speed	30°/S
Horizontal Rotation Range	0°~360°
Tilt Rotation Speed	15°/S
Tilt Rotation Range	0°~93°
Preset Points	255
Guard Tours	8 groups
Guard Points	Max 20 points
Lens	
Focus Length	5.35-96.3mm F1.8-F3.9
Focus Control	18X Optical Zoom
Night Vision	
Infrared LED	Ø 35x6PCS
IR Range	80m
Day-night mode	AUTO
Network	
Network protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, SMTP
ONVIF	Support (PROFILE S, PROFILE T)
Network interface	Built-in RJ45 network interface, support 10M/100M IP DATA

Main Stream1	5MP(2592*1944)@20fps
Main Stream2	4MP(2560*1440)@25fps
Main Stream3	1080P(1920*1080)@30fps
Main Stream4	720P(1280*720)@30fps
Main Stream5	N/A
Main Stream6	N/A
Sub Stream1	D1(720*480)@20fps
Sub Stream2	CIF(352*288)@20fps
Sub Stream3	N/A
Sub Stream4	N/A

AI Function	
Intelligent Analysis	3D Human Tracking(Effective Range:5~50M ,Speed: 3~12KM/h) / Motion detection based on human detection/ Intrusion Detection based on human detection

Camera Features	
Day/Night	Color/ B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control), Video Tampering, Distortion
Full Color	N/A
Corridor Pattern	N/A
Defog Mode	Support
ROI	Support
BLC	Support
WDR	120dB(Not support in 5MP resolution)
Motion Detection	Support(support enable the detection based on human movement only)
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Arabic, German, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands,Czech, Vietnamese

Interface	
Audio	Internal Audio and built-in speaker
Audio Encode	G711A, C711U
Alarm	N/A
SD Card Slot	Internal SD card.
POE	Yes

General	
Weatherproof	IP66
Operating Temperature	Light on: -20~45℃ Light off:-20~55℃
Operating Humidity	≤90% Non Condensing
Power	DC12V/1.2A(Device power consumption) DC12/3A(Power supply)
Lightning Protection	Transient voltage 6000V
Dimension	device:136*136*230(mm) package:185*185*285(mm)
Weight	device:1.56Kgs package:2.24Kgs