



SPECIFICATION

| | | |
|----------------------|--|---------------|
| Model NO. | CMSBHTC500FKE | CMSBTHC500FKE |
| Video Output Mode | AHD: 8M@15fps, 5M@20fps/12.5fps, 4M@30fps/25fps/15fps, 2M@30fps/25fps; TVI: 8M@15fps/12.5fps,5M@20fps/12.5fps,4M@30fps/25fps/15fps, 2M@30fps/25fps; CVI: 8M@15fps/12.5fps,4M/2M@30fps/25fps;CVBS | |
| Camera | | |
| Image Sensor | 1/2.5" CMOS sensor | |
| Image Resolution | 8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080 | |
| TV System | PAL/NTSC | |
| Electronic Shutter | Auto | |
| Minimun Illumination | Color : 0.03 lux@F2.0, AGC ON; B/W : 0 lux with IR | |
| Scanning System | Progressive Scan | |
| Lens | | |
| Focus Length | 2.8mm | |
| Focus Control | Fixed | |
| Lens Type | Fixed | |
| Night Vision | | |
| IR Cut Filter | YES | |
| Infrared LED | 42μ x 2PCS | |
| Infrared Distance | 25M | |
| IR Status | AGC Auto Control | |
| Camera Features | | |

| | |
|-----------------|----------------|
| Starlight | N/A |
| Day/Night | YES |
| OSD Menu | YES |
| WDR | DWDR |
| UTC | YES |
| Noise Reduction | DNR |
| Coaxial Audio | YES(only TVI) |
| White Balance | AUTO / MANUAL |
| Gain Control | AUTO |

General

| | |
|-----------------------|-----------------------|
| Housing | Metal, IP67 |
| Bracket | NO |
| Operation Temperature | -10℃ ~ +60℃ RH95% Max |
| Storage Temperature | -20℃ ~ +60℃ RH95% Max |
| Power Source | DC12V±10%, 500mA |
| Dimension | ∅ 96 x 91(H) mm |
| Weight | 600g |