

machpower®

Vivavoce interattivo per conferenze

EB-PICAS





**massima
qualità
audio**

Principali Caratteristiche

- 1 microfono omni-direzionale integrato composto da 3 microfoni in silicone.
- 1 ingresso lineare con eliminazione dell'eco, tramite wireless 2.4G o ingresso cavo USB
- 1 uscita lineare con eliminazione dell'eco eco tramite wireless 2.4g o cavo USB;
- 1 uscita audio standard da 3.5 mm per altoparlanti esterni.
- 1 uscita audio stereo tramite interfaccia audio standard da 3.5 mm;
- Tecnologia full-band e full-duplex adattiva per l'eliminazione dell'eco;
- Tecnologia full-band adattiva e dinamica di riduzione del rumore fino a 18dB;
- Frequenza 48 kHz, A / D e D / A, 24 bit.
- Trasmissione dati tramite wireless 2.4g (priorità) e USB;
- Alimentazione a batteria, ricarica tramite cavo USB;
- Touch screen per accensione / spegnimento, disattivazione microfono e volume altoparlante;
- Altoparlante incorporato

Specifiche Tecniche

Frequency Response	20Hz-16kHz
Loudspeaker	Built-in speaker, automatic gain control provides smooth audio output
SNR	65dB
Echo cancellation	Adopt industry's leading echo cancellation technology
Noise suppression	Denoise level can be 18dB
Automatic gain control	±6dB
Sampling frequency	32kHz
Built-in MIC pickup radius	The maximum pickup distance of omnidirectional is 8 meters, and the best pickup distance is 3~5 meters
Transmission mode	2.4g wireless (preferred) /USB cable
Audio output interface	3.5mm headphone jack
Monitor interface	3.5mm headphone jack
Charge jack	Mini USB
Firmware upgrade interface	Mini USB
Control mode	Button control, touch screen
Key function	Power on/off,mute button/volume down/up,default settings
Indicator light	Two-color LED indicator light; Power indicator and operation indicator (charging state, low power state, normal working state, wireless / USB state)
AC Adapter	DC5V±0.2V, 1A
Battery	Charging time: about 4 hours, Using time: about 12 hours
Stand-by time	3 months
Operating temperature	0-50°C
Storage temperature	-20-60°C
Working humidity	5% ~ 95% R.H.
Storage humidity	0 ~ 95% R.H.
Size	Φ122 x 39mm
Net Weight	≤ 500g